

EACIL20

Intel® Celeron® N3350 fanless computer



KEY FEATURES

- Intel® Apollo Lake N3350 1.1 GHz fanless computer
- Fanless cooling system
- Compact size 100 x 70 x 31 mm(w/o mounting bracket)
- Expansion module design
- Various mounting options: desk, wall, VESA, DIN-Rail
- AWS IoT Greengrass Certified



SPECIFICATIONS

System Specification			
Processor	Intel® Celeron® N3350 (2M Cache, up to 2.4 GHz) Intel® Pentium® N4200 (2M Cache, up to 2.5 GHz) (Optional)	Memory	4GB LPDDR4 2400 MHz
Storage	eMMC: Onboard 32 GB Onboard 64 GB (Optional) Onboard 128 GB (Optional) mSATA SSD 64GB (Optional)	Ethernet controller	2 x Intel® Ethernet Controller
Security	TPM 2.0	Operating System	Windows 10 IoT Enterprise (Optional) Linux Ubuntu 18.04 (Optional)
WLAN	Support (Optional)	BT	Support (Optional)
WWAN	WWAN (Optional)	Expansion Port	EACWSLT-222 WWAN Expansion Board (Single SIM Slot) EACWSLT-231 3-port RS232/422/485 w/ isolation EACWSLT-232 16-Channel Digital I/O w/ isolation EACWSLT-233 2-port CANBUS w/ isolation EACWLST-234 3 -port USB 2.0 EACWLST-235 2-port RS232/422/485 w/ isolation EACWLST-236 2-port Giga-LAN EACWLST-237 WWAN Expansion Board (Dual SIM Slot)
Mechanical			
Dimension	100 (W) x 70 (H) x 31(D) mm(One layer) 100 (W) x 70 (H) x 61(D) mm(Double layer)	Mounting	Desk Mounting & Wall Mounting VESA Mounting (Optional) DIN-Rail Mounting (Optional)
Enclosure	Metal Housing	Cooling System	Fanless design
Environment			
Operating Humidity	30% to 90% (non-condensing)	Operating Temperature	0~55°C
Storage Temperature	-15~70°C	Shock	Operating, IEC 60068-2-27
Vibration	Operating, IEC 60068-2-64	IP rating	IP30
Certification			
Certification	CE, FCC Microsoft Azure Certified for IoT AWS IoT Greengrass Certified		
IO Ports			

Power Input	1 x 9~36V DC, 2-Pin Terminal Block	USB Port	2 x USB3.0 (Type-A)
Video	1 x HDMI 1.4 (Optional)	Expansion Port	mPCIe: 1 x Full-size mPCIe slot USB Wafer : 2 x USB Wafer
LAN	2 x Giga LAN RJ45 Connector	Indicator	1 x LED Indicator for power
mini PCIe	1 x Mini PCIE		

Control

Button	1 x Power Button 1 x Reset Button
---------------	--------------------------------------

Accessory

Accessory	Quick Start Guide Driver CD Terminal Block 2 pin to 2.5Ø Female Adapter Cable Open Wire Cable with terminal block 2 pin connector WLAN External Antenna (For WLAN sku) WWAN External Antenna (For WWAN sku) AC to DC Adapter 12V/36W (Optional) VESA Mounting Kit (Optional) DIN Rail Mounting Kit (Optional)
------------------	--

Power


Power Rating	9V~36V DC, 2-Pin Terminal Block	Adapter	12V 36W
---------------------	---------------------------------	----------------	---------

Ordering Information

Option	EACWSLT-222 WWAN Expansion Board (Single SIM Slot) (Optional) EACWSLT-231 3-port RS232/422/485 w/ isolation (Optional) EACWSLT-232 16-Channel Digital I/O w/ isolation (Optional) EACWSLT-233 2-port CANBUS w/ isolation (Optional) EACWSLT-234 4-port USB 2.0 (Optional) EACWSLT-235 2-port RS232/422/485 w/ isolation (Optional) EACWSLT-236 2-port Giga-LAN (Optional) EACWSLT-237 WWAN Expansion Board (Dual SIM Slot) (Optional)
---------------	--

DIMENSIONS UNIT:MM

Winmate fanless computer EACIL20



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.