

R6H-300A

LCD Scaler Board (1920 x 1200, VGA + HDMI)



KEY FEATURES

- Supports resolution 1920 x 1200 @ 60 Hz
- 12 V DC Input
- VGA support Sync-On-Green (SOG)
- HDCP 1.2 Enhanced protection of HDCP secret key
- Built-in stereo audio device (Optional)
- IR remote control (Optional)
- Operating Temperature 0°C~+50°C
- Storage Temperature -20°C~+60°C




SPECIFICATIONS

System			
Support Panel Interface	LVDS (8-bit)	Resolution	1920x1200
IO Ports			
Video	1 x VGA 1 x HDMI 1.4		
Certification			
Certification	CE, FCC		
Environment			
Operating Humidity	10% to 90% (Non-Condensing)	Operating Temperature	0~50°C
Storage Temperature	-20°C~60°C		
Power			
Power Rating	12V DC input		

DIMENSIONS UNIT:MM

Winmate R6H-300A



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. All specifications are subject to change without prior notice.
4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.