

W42L300-65A3

42" IP65 Stainless Chassis Display



KEY FEATURES

- 42", 1920 x 1080 IP65 Stainless Chassis Display
- Chassis
- VESA mount
- Stainless housing SUS 316 / AISI 316
- Full IP65 waterproof and dustproof



SPECIFICATIONS


Display	
Resolution	1920x1080
Contrast Ratio	4000:1
Display Color	1.07B Colors
Active Area	930.24x523.26 mm
Size	42 inches
Panel Brightness	500 nits
View Angles	89,89,89,89
Touch / Glass	Protection Glass
Mechanical	
Dimension	1046 x 633 x 64.6 mm
Enclosure	Stainless Housing
Mounting	VESA Mount
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% (non-condensing)
Storage Temperature	-20~60°C
Operating Temperature	0~45°C
IP rating	IP65
Certification	
Certification	CE, FCC
IO Ports	
Power Input	1 x M12 waterproof connector for 24V DC
Video	1x M12 type connector for VGA input 1x waterproof DVI input (Optional) 1x waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power 1 x LED Indicator for status
Control	
Button	1 x Power Button 1 x Adjust up button 1 x Adjust down button 1 x ESC (Auto) button 1 x OK (Menu) button
Accessory	
Accessory	100~240V AC to DC Adapter with waterproof connector Power Cord External VGA cable with waterproof connector Waterproof caps Manual VESA screws
Optional Accessory	External HDMI cable with waterproof connector (Optional) External DVI cable with waterproof connector (Optional) External Power cable with waterproof connector (For AC power build in) (Optional)

Power

Power Rating 24V DC (M12 type)

DIMENSIONS UNIT:MM

Winmate W42L300-65A3



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. All specifications are subject to change without prior notice.
4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.